

Product Data

Castrol Classic TQF

Automatic Transmission Fluid for Classic Vehicles

Description

Classic TQF is an automatic transmission fluid specially formulated from high quality mineral oils and incorporates various additives to provide wear, oxidation and corrosion resistance. The product is dyed red to distinguish it from crankcase oils should leakage occur.

Application

Classic TQF was specically formulated to meet the requirements of the now obsolete Ford automatic transmission fluid (ATF) specification ESW-M2C-33G / -33F as required for many older transmission used in classic vehicles. It may also be used as a general hydraulic fluid or power steering fluid where the Manufacturer specifies the use of an ATF. It should not be used where MERCON[®] or DEXRON[®] type fluid required.

Typical Characteristics

Name	Method	Units	Classic TQF
Density @ 15C, Relative	ASTM D4052	g/ml	0.865
Colour	Visual	-	red
Viscosity, Kinematic 40C	ASTM D445	mm²/s	38
Viscosity, Kinematic 100C	ASTM D445	mm²/s	7.4
Viscosity Index	ASTM D2270	None	165
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	30900
Flash Point, COC	ASTM D92	°C	-
Pour Point	ASTM D97	°C	-45

Product Performance Claims

Meets - Ford ESW-M2C-33F/ ESP-M2C-33G

Castrol Classic TQF 19 Jan 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com