



# RAVENOL ATF 5/4 HP Fluid

**Kategorie:** Gear oil for automatic transmissions

**Artikelnummer:** 1212104

**Oil type:** Synthetic

**Recommendation:** Alfa Romeo 20HP 14891900, ATF LA 2634, ATF LT 71141, BMW 83229407765, BMW 83229407807, Citroën/Peugeot AL4 PR 9736.22, Jaguar JLM 20237, Land Rover STC4863, MB 236.11, Mercedes A 001 989 22 03, Porsche 999.917.547.00, Renault DP0, VW TL 52162, VW/Audi G 052 162 A1, VW/Audi G 052 162 A2, VW/Audi G 052 162 A6, ZF S671 090 170

**Application:** Passenger car



**RAVENOL ATF 5/4 HP Fluid** is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

**RAVENOL ATF 5/4 HP Fluid** is ATF (Automatic Transmission Fluid) for all 4- and 5 stroke automatic transmissions of ZF. It guarantees in any mode for maximum wear protection.

**RAVENOL ATF 5/4 HP Fluid** is natural brown colored.

1L | 1212104-001

4L | 1212104-004

10L | 1212104-010

20L | 1212104-020

20L | 1212104-B20

60L | 1212104-060

60L | 1212104-D60

208L | 1212104-208

208L | 1212104-D28

1000L | 1212104-700

## Application Note

**RAVENOL ATF 5/4 HP Fluid** is suitable for use in automatic transmission of ZF Serie 4 HP (4HP20, 4HP22, 4HP24) und 5HP (5HP18, 5HP19, 5HP24, 5HP30). Maintenance-filling under normal operating conditions.

## Characteristics

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	849,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Pourpoint	°C	-54	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

RAVENOL special transmission fluids are special developments for special gears and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. If you are unsure about the right transmission fluid, ask your workshop or dealership for advice on the transmission type and OEM original number or ask our experts, making sure to state the VIN code (vehicle identification number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH is not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.

10.07.2022