



# RAVENOL ATF Dexron D II

**Kategorie:** Gear oil for automatic transmissions

**Artikelnummer:** 1213102

**Specification:** Allison C3, Allison C4, GM Dexron®-IID

**Oil type:** Mineral

**Approvals:** Voith H55.6335.xx

**Recommendation:** Caterpillar TO-2, CVT, Ford M2C-138 CJ, Ford M2C-166H, Ford M2C-185A, Ford MERCON®, Ford SQM-9010B, MAN 339 Z1, MB 236.6, MB 236.7, Renk Doromat, ZF TE-ML 03D, ZF TE-ML 04D, ZF TE-ML 05L, ZF TE-ML 11A, ZF TE-ML 14A, ZF TE-ML 17C

**Application:** Passenger car, Truck, Oldtimer



**RAVENOL ATF Dexron D II** is a first class transmission fluid for automatic transmissions of all vehicles and working machines on the basis of high refined mineral oils with a corresponding additive treatment.

## Application Note

**RAVENOL ATF Dexron D II** was developed for the use in automatic transmissions, hydro steering mechanisms, converters and power transmissions and can be used as a universal ATF (Automatic-Transmission-Fluid) for all vehicles and working machines.

## Characteristics

- protection against corrosion, sludge and sticking
- an excellent and very shear stable viscosity temperature behaviour
- no problems concerning very low respectively very high temperatures
- an excellent high thermal capacity
- free of foam even under hardest loads
- neutral behaviour against sealing materials
- mixable and compatible with all kinds of ATF

**1L | 1213102-001**

**4L | 1213102-004**

**10L | 1213102-010**

**20L | 1213102-020**

**20L | 1213102-B20**

**208L | 1213102-208**

**208L | 1213102-D28**

**1000L | 1213102-700**

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	848,0	EN ISO 12185
Colour		Rot	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	7,3	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	34,3	DIN 51562-1
Viscosity Index VI		185	DIN ISO 2909
Pourpoint	°C	-51	DIN ISO 3016
Flashpoint	°C	210	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.

10.07.2022